

Calculez et dimensionnez vos câbles électrique :

[illegible]

P en KW	I en A	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240
1	3	165	280	445	655											
1,5	5	110	185	295	440	725										
2	7	84	140	220	325	540	850									
2,5	8	67	110	175	265	435	675									
3	10	58	95	145	220	365	560	870								
3,5	12	48	78	125	190	315	485	740								
4	13	43	68	110	165	275	425	650	905							
4,5	15	37	61	97	145	245	375	580	820							
5	17	33	54	86	130	220	340	520	730	905						
6	20		46	73	110	185	285	435	610	760						
7	23		40	63	94	160	245	370	520	650	920					
8	26			56	82	140	215	325	450	575	795					
9	30			49	73	125	190	290	405	510	710					
10	33				65	115	170	260	365	465	640	840				
12	40				54	94	140	220	305	385	530	700				
14	46					80	120	185	260	335	460	600	715			
16	53					68	105	165	225	290	400	525	630	725		
18	59						94	145	200	260	360	470	560	640		
20	66						85	130	180	235	320	420	500	575	680	
25	82							105	145	190	260	340	400	460	540	645
30	98								120	160	215	280	335	390	450	540
35	115								100	135	185	240	290	330	385	465
40	131									115	160	210	250	290	340	405
45	148										145	185	220	260	300	360
50	164										130	170	200	230	270	325
60	197											140	165	195	225	270
70	230												140	165	195	230
80	263													145	170	205
90	296														150	180
100	328															160
110	361															145

Limite
de
chauffe

220 tri

P en KW	I en A	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240
2,5	5	190	325	510	745											
3	6	160	270	420	620											
3,5	7	135	230	365	540	895										
4	8	120	200	320	470	785										
4,5	9	105	180	285	420	700										
5	10	96	165	255	375	630	970									
6	12	79	135	210	315	525	810									
7	14	68	115	180	270	455	700									
8	16	60	105	160	240	400	610	940								
9	18	51	92	145	215	355	550	850								
10	19		84	130	190	320	500	780								
12	23		69	110	160	265	415	640	880							
14	27			94	140	230	355	550	750							
16	31			81	120	200	315	485	655	860						
18	35				110	180	280	430	580	770						
20	38				98	160	255	390	520	690						
25	48					130	205	315	420	555	760					
30	57						170	260	355	465	640	840				
35	67						145	225	300	400	550	730				
40	76							195	260	350	480	640	745			
45	86							175	235	310	430	565	670	770		
50	95							160	215	285	385	510	600	695		
60	114								180	235	320	420	500	580	680	
70	133									200	275	365	430	495	580	
80	152										240	315	375	430	510	600
90	171										215	280	335	385	445	535
100	190											250	300	350	405	480
120	228												250	290	340	400
140	266													250	290	345
160	304														255	300
180	342															265

Limite
de
chauffe

380 tri













